

PANTHER WEB DEBUGGER

Panther's Web debugger provides you the ability to view and analyze all JPL source in a Panther Web application. You can:

- Step through JPL, stopping to examine data.
- Set breakpoints in JPL code on which to interrupt program execution.
- Examine application data in JPL variables, JPL arrays or expressions.
- Review tracing activity in the log file. Tracing messages can also be written to a user-specified log file.

Installing and configuring Panther/Web Debugger Win32

Prerequisite

A Panther/Web application to debug, Eclipse and Apache

Download

Download Panther Web Debugger from <https://github.com/ProlificsPanther>

Eclipse & Apache Tomcat

- i. Install a later version of Eclipse- 32bit
- ii. Please setup Apache Tomcat as a Test Server in Eclipse UI. [Click for steps.](#)

Add JAR files to CLASSPATH in Panther/Web ini file

- i. prowebdbg.jar
- ii. tyrus-standalone-client-1.13.1.jar
- iii. websocket-api.jar
- iv. javax.json-api-1.0.jar
- v. javax.json-1.0.4.jar
- vi. pro5.jar. See use the exact version from \$SMBASE/config

Update Panther/Web ini file

1. WebSocketClass= com.prolifics.websocket.DebugMessenger
2. NumServers=1
3. IdleServerTimeout= <set to blank>
4. ServerTimeout= <set to blank>

Enable tracing in your application

To enable tracing, execute the below call in your very first JPL screen of your application, or in a JPL file that is loaded when your application first starts, .i.e. file point to by SMINITJPL

```
call sm_trace("ALL websocket=default")
```

Import Debugger zip File

1. Import Gen*. zip project into your workspace:
2. File->Import...
3. General->Existing Projects into Workspace
4. Next
5. Choose the 'Select archive file' radio button
6. Browse...
7. Finish

Fix Java Build Path and export prowebdbg.jar

1. After importing the project, edit the Libraries used in Java Build Path by correcting the locations of the JAR files on your machine. Right click on the Project -> Properties->Java Build Path
2. Verify that the code can be rebuilt by cleaning the project and rebuilding
3. Export the project as a java jar file to the location where your **prowebdbg.jar** is present and replace that jar with your project.
4. Add Web Module Gen* to Tomcat Server

*If you have conflicting port numbers, please chose an available port number.

Test the Debugger

1. Enter this URL to access the Debugger <http://localhost:8085/Gen2a/Debugger>
2. Next add the applications' URL to the Application URL field, .i.e. <http://localhost/hr/login.jam> , then press Go.
3. The Application will open in the next Browser Tab

How to use the debugger

Windows

Status Window

Contains all the trace details, events, JPL, line numbers etc. This is what the JServer processes.

Breakpoint Window

Choose the breakpoint type here.

Data Watch Window

Ability to introspect values of variable/fields.

JPL Module Window

In this window you will be able to see the name of the **JPL** file that us executing. When **breakpoints** are set, you can navigate to this **window** and check to see which **JPL** file is being executed.

Buttons

Play (Continue to next break point)

As the name indicates this button helps us continue to the **next breakpoint**.

- For example, if we have set **3 breakpoints**, once we start **debugging**, it will **stop** at the **1st breakpoint**; if we want to inspect the **JPL** line by line, select the **step in** button (**2nd from Left**) OR use the **Play** button to continue to the **next break point** ignoring the remaining JPL code.
- If only **1 breakpoint** is set and when it stops at that **breakpoint**, if we choose **Play**, it takes us to the end of that **JPL** file, which specifies that we don't have any further **breakpoints** set.

Step In (Continue to next event)

Allows you to debug JPL within a particular JPL procedure that you have previously set as a breakpoint.

Step Over (Steps over a proc)

Let's you step over a particular **JPL** procedure that was set as a breakpoint.

Break (Breaks at next event)

This button helps to break our trace where ever and whenever needed.

- If you have not set any breakpoints and you wish to check the code line by line using the **Step in** button (2nd from the left), you can click the **Break** button and perform any Panther event. The **Play**, **Step In and Step over** buttons are enabled from there and you can do either of the below:
 - Step In line by line
 - Step Over at the end of proc if a proc has started

Start/Stop Tracing Debugger (Toggle debug mode)

The button with the Bug image allows you to **start\stop** tracing. By default, tracing is turned on; i.e. Bug is **Green**. To stop tracing, toggle the button and it will change to Red which indicates that tracing has **stopped**.

Setting Breakpoints

- Select the breakpoint **type** for which you need to set a breakpoint
- If the type you choose is **Any Jpl**, provide a **proc** name in the **location** field, which is the name of your **JPL** procedure. Then you can proceed with the "**Play Button** or **Step over** button" to continue further.
- If the type you choose is a **JPL Module** you will have to provide the **JPL** file name for which you want to set a breakpoint in.
 - If you want to set a breakpoint in a **proc**, enter a **JPL proc** name in the **location** field
- If you need to set a breakpoint for a line number please enter a **line number** and Press **enter**.
- To continue debugging, click on the **Play** or **Step Over** button.

Watching Data

In this section you need to enter the name of a field/variable that you like to view its value.

- Set a breakpoint, enter a variable name in the "Variables & Expressions" tab and click the **Play** button.
- Tracing will stop at the breakpoint. Click the **Step In** button. As you trace the JPL, you will be able to view the value of that variable in this window.
- A "?" value indicates that the variable/jpl has no value.

NOTE:**Once you set a Breakpoint you must continue Debugging; i.e. hit Play/Step Over. Breakpoints are NOT saved when you refresh the browser.

Headquarters

**24025 Park Sorrento, Suite 405
Calabasas, CA 91302
P: 818.582.4952 / F: 818.224.5269**

NEW YORK

5 Hanover Square,
Suite 2001
New York, NY 10004

WESTBURY

865 Merrick Avenue
Suite 105
Westbury, NY 11590

ORLANDO

20 North Orange Avenue, Suite 1211
Orlando, FL 32801
P: 407.641.0800
F: 407.420.9484

PLEASANTON

7041 Koll Center Parkway, Suite 135
Pleasanton, CA 94566
P: 408.653.2020

BERKSHIRE

Suite 1-10 | SoanePoint
6-8 Market Place
Reading | Berkshire RG1 2EG
United Kingdom

HAMBURG

Rodingsmarkt20
20459 Hamburg
Germany
P: +49 (0)40 890 667-88
F: +49 (0)40 890 667-99

OTTAWA

100-237 Argyle Avenue
Ottawa, ON K2P 1B8
P: 866.639.1451

TORONTO

100 King Street West
Suite 5600
Toronto, ON M5X 1C9

INDIA

Hyderabad (Registered Office)
5th Floor,
DHFLVC Silicon Towers,
Survey No 14, Kondapur, Hyderabad - 500032

Plot #226, Road #17
Jubilee Hills, Hyderabad - 500033
P: +91 40 39991999 / +1 818 301 4945
F: +91 40 23114651

8th Floor, Block - 3
Plot #229-232, APHB Colony
DLF Commercial Developer Ltd. SEZ
Gachibowli Village, Hyderabad - 500029

9th Floor, Building # 20
MindSpace SEZ,
K. Raheja IT Park Pvt. Ltd, HITEC City
Madhapur, Hyderabad - 500081

Cerebrum IT Park
Units 1&2, First Floor, Building# B3
Kalyaninagar, Pune - 411014

TVK Industrial Estate
7th Floor, R R Towers - III
Guindy, Chennai, TN - 600032